



Technische Daten	GO 1301
Fühlertyp / Toleranzklasse	K-NiCr-Ni / DIN EN 60584 Klasse 2
technischer Messbereich	gerader Bandfühler bis 500°C
empfohlener Messbereich	-200 bis 500°C
Messmethoden	Oberflächenmessung
Einsatzgebiete	Kunststoffindustrie- Oberflächentemperatur vom Walzgut. Autoindustrie- Temperaturmessung an der Bremsscheibe Flachglasproduktion- Prüfung der Aufdampftemperatur(Glas veredelung)
Einstellzeit	2 Sek. (Einstellzeit:T99)
Abmessungen Fühler	Ø = 15mm Länge 63mm
Kabel / Länge	Spiralkabel / 1,8m
CE - Zeichen	entspricht EU-Richtlinien über elektromagnetische Verträglichkeit
Bestellnummer	3 741 130

Technical Data	GO 1301
Sensor type / tolerance class	K-NiCr-Ni / DIN EN 60584 class 2
technical measuring range	straight tape sensor up to 500 °C
recommended measuring range	-200 to 500 °C
Measuring functions	Surface measurement
Areas of application	Plastics industry surface temperature of the rolled material. Car industry - temperature measurement on the brake disc flat glass production - test of the vapor deposition temperature (glass finishing)
Setting time	2 sec. (response time: T99)
Dimensions sensor	Ø = 15mm length 63mm
Cable / length	Spiral cable / 1.8m
CE - label	corresp. EU rules about electromagnetic immunity
Item number	3 741 130